
























Axis fixed dome network cameras

| | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor / Outdoor |
|--|--|--|---|---|--|---|---|---|---|
| | AXIS 209FD  | AXIS 209FD-R  | AXIS 209MFD  | AXIS 209MFD-R  | AXIS M3011  | AXIS 216FD AXIS 216FD-V  | AXIS 216MFD AXIS 216MFD-V  | AXIS P3301 AXIS P3301-V  | AXIS 225FD AXIS 225FD 22 mm  |
| Image sensor | 1/4" progressive scan CMOS | 1/4" progressive scan CMOS | 1/3" progressive scan CMOS 1.3 megapixel | 1/3" progressive scan CMOS 1.3 megapixel | 1/4" progressive scan CMOS | 1/4" progressive scan CMOS | 1/3" progressive scan CMOS 1.3 megapixel | 1/4" progressive scan CMOS | 1/4" progressive scan CCD |
| Lens | 3.0 mm/F2.0 fixed iris | 3.0 mm/F2.0 fixed iris | 3.6 mm/F1.8 fixed iris | 3.6 mm/F1.8 fixed iris | 3.0 mm/F2.0 fixed iris | Varifocal 2.8 - 10 mm/F1.3 DC-iris | Varifocal 2.8 - 10 mm/F1.3 DC-iris | Varifocal 2.8 - 10 mm/F1.3 DC-iris | Varifocal, DC-iris Standard: 2.8 - 5.8 mm/F1.4 22 mm: 9 - 22 mm/F1.5 |
| Day and night | | | | | | | | | Automatic |
| Min illumination/ light sensitivity (lux) | 1.5 - 10,000 | 1.5 - 10,000 | 3 - 10,000 | 3 - 10,000 | 1 - 10,000 | 1 | 2 | 1 | Standard: 1 (color), 0.2 (B/W) 22 mm: 1.5 (color), 0.3 (B/W) |
| Compression | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | H.264, Motion JPEG MPEG-4 | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | H.264, Motion JPEG | MPEG-4 Motion JPEG |
| Max video resolution (pixels) | 640 x 480 | 640 x 480 | 1280 x 1024 | 1280 x 1024 | 640 x 480 | 640 x 480 | 1280 x 1024 | 640 x 480 | 640 x 480 |
| Frames per second | 30 (640x480) | 30 (640x480) | 12 (1280x1024) | 12 (1280x1024) | 30 (640x480) | 30 (640x480) | 12 (1280x1024) 30 (800x600) | 30 (640 x 480) | 30 (640x480) |
| Audio support | | | | | | Two-way, Half Duplex | Two-way, Half Duplex | Two-way, Half Duplex | |
| Alarm in-/outputs | | | | | | 1/1 | 1/1 | 1/1 | 2/1 |
| Intelligent video | Motion detection | Motion detection Active tampering alarm | Motion detection | Motion detection Active tampering alarm | Motion detection Active tampering alarm | Motion detection Audio detection Active tampering alarm | Motion detection Audio detection Active tampering alarm | Motion detection Audio detection Active tampering alarm | Motion detection Active tampering alarm |
| Security | Multi-level passwords IP filtering HTTPS encryption | Multi-level passwords IP filtering HTTPS encryption | Multi-level passwords IP filtering HTTPS encryption | Multi-level passwords IP filtering HTTPS encryption | Multi-level passwords IP filtering HTTPS encryption | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X |
| Network | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS |
| Power over Ethernet (IEEE 802.3af) | Class 1 | Class 1 | Class 1 | Class 1 | Class 1 | Class 1 | Class 1 | Class 2 | Class 2 (without heater) |
| Serial connectors | | | | | | | | | RS-485 |
| Outdoor use | | | | | | | | | ● |
| Other | Tamper-resistant | IP66-rated, rugged, for mobile video surveillance | Tamper-resistant | IP66-rated, rugged, for mobile video surveillance | Recessed mounting | AXIS 216FD: Tamper-resistant AXIS 216FD-V: Vandal-resistant | AXIS 216MFD: Tamper-resistant AXIS 216MFD-V: Vandal-resistant | WDR, Tamper-resistant | Vandal-resistant, IP66-rated, heater and fan |
| Axis part # | 0281-004 | 0275-004 | 0283-004 | 0286-004 | 0284-004 | AXIS 216FD: 0240-004 AXIS 216FD-V: 0268-004 | AXIS 216MFD: 0278-004 AXIS 216MFD-V: 0279-004 | AXIS P3301: 0290-004 AXIS P3301-V: 0292-004 | AXIS 225FD: 0243-004 AXIS 225FD 22mm: 0243-064 |
| MSRP (USD) | \$499 | \$599 | \$599 | \$699 | \$549 | AXIS 216FD: \$629 AXIS 216FD-V: \$669 | AXIS 216MFD: \$729 AXIS 216MFD-V: \$769 | AXIS P3301: \$679 AXIS P3301-V: \$719 | \$999 |

Axis fixed network cameras – Indoor




| | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor |
|---|--|---|--|--|--|---|--|
| | AXIS 206  | AXIS 207/ AXIS 207W  | AXIS 207MW  | AXIS M1011/ AXIS M1011-W  | AXIS M1031-W  | AXIS 210/ AXIS 210A  | AXIS P1311  |
| Image sensor | 1/4" progressive scan CMOS | 1/4" progressive scan CMOS | 1/3" progressive scan CMOS 1.3 megapixel | 1/4" progressive scan CMOS | 1/4" progressive scan CMOS | 1/4" progressive scan CCD | 1/4" progressive scan CMOS |
| Lens | 4.0 mm/F2.0 fixed iris | 4.0 mm/F2.0 fixed iris | 3.6 mm/F1.8 fixed iris | 4.4 mm/F2.0 fixed iris | 4.4 mm/F2.0 fixed iris | 4.0 mm/F1.2 fixed iris CS mount | 4.0 mm/F1.2 fixed iris, CS mount |
| Day and night | | | | | | | |
| Min illumination/light sensitivity (lux) | 4 - 10,000 | 1 - 10,000 | 2 - 10,000 | 1 - 10,000 | 1 - 10,000 0 with LED on | 1 - 10,000 | 0.6 - 30,000 |
| Video compression | Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | H.264, Motion JPEG MPEG-4 | H.264, Motion JPEG MPEG-4 | MPEG-4, Motion JPEG | H.264, Motion JPEG, MPEG-4 |
| Max video resolution (pixels) | 640 x 480 | 640 x 480 | 1280 x 1024 | 640 x 480 | 640 x 480 | 640 x 480 | 640 x 480 |
| Frames per second | 30 (640x480) | 30 (640x480) | 12 (1280 x 1024) | 30 (640x480) | 30 (640x480) | 30 (640x480) | 30 (640 x 480) |
| Audio support | | One-way | One-way | | Two-way, built-in mic and speaker | 210A: Two-way, Full Duplex | Two-way, built-in mic, Half Duplex |
| Alarm in-/outputs | | 1/1 | 1/1 | | | 1/1 | 1/1 |
| Intelligent video | | Motion detection Audio detection | Motion detection Audio detection | Motion detection Tampering alarm | Motion detection Audio detection Tampering alarm | Motion detection | Motion detection Audio detection Tampering alarm |
| Security | Multi-level passwords | Multi-level passwords IP filtering ⁴ HTTPS encryption ⁴ IEEE 802.1X ⁴ | Multi-level passwords IP filtering HTTPS encryption | Multi-level passwords IP filtering HTTPS encryption | Multi-level passwords IP filtering HTTPS encryption | Multi-level passwords IP filtering HTTPS encryption ⁵ IEEE 802.1X ⁵ | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X |
| Network | IPv4 | IPv4 | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS |
| Power over Ethernet (IEEE 802.3af) | PoE splitter available #5008-001 | PoE splitter available #5008-001 | PoE splitter available #5008-001 | PoE splitter available #5008-001 | PoE splitter available #5008-001 | AXIS 210: PoE splitter AXIS 210A: Class 2 | Class 1 |
| Serial connectors | | | | | | | |
| Outdoor use | | | | | | | |
| Other | | | Wireless 802.11g/b | AXIS M1011-W: Wireless IEEE 802.11b/g | Built-in PIR sensor and illumination LED, Wireless 802.11g/b | Changeable lens | SD/SDHC memory card slot |
| Axis part # | 0199-004 | AXIS 207: 0235-004 AXIS 207W: 0241-004 | 0264-004 | AXIS M1011: 0302-004 AXIS M1011-W: 0301-004 | 0300-004 | AXIS 210: 0197-004 AXIS 210A: 0233-004 | 0293-004 |
| MSRP (USD) | \$199 | AXIS 207: \$279 AXIS 207W: \$299 | \$399 | AXIS M1011: \$179 AXIS M1011-W: \$199 | \$279 | AXIS 210: \$449 AXIS 210A: \$549 | \$599 |

Axis fixed network cameras – Indoor / Outdoor

| | Indoor / Outdoor | Indoor / Outdoor | Indoor / Outdoor | Indoor / Outdoor | Indoor / Outdoor | Indoor / Outdoor | Indoor / Outdoor |
|---|--|---|---|---|--|---|--|
| | AXIS 211¹  | AXIS 211A¹  | AXIS 211W¹  | AXIS 211M¹  | AXIS 221¹  | AXIS 223M¹  | AXIS Q1755¹  |
| Image sensor | 1/4" progressive scan CCD | 1/4" progressive scan CCD | 1/4" progressive scan CMOS | 1/3" progressive scan CMOS 1.3 megapixel | 1/3" progressive scan CCD | 1/2.7" progressive scan CCD 2 megapixel | 1/3" progressive scan CMOS 2 megapixel |
| Lens | Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount | Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount | Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount | Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount | Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount | Varifocal 4.0 - 8.0 mm/F1.4 DC-iris, C mount ¹ | 5.1 - 51 mm/F1.8 auto iris and autofocus 10x optical zoom 12x digital zoom |
| Day and night | | | | | Automatic | Automatic | Automatic |
| Min illumination/light sensitivity (lux) | 0.75 | 0.75 | 0.75 | 1 | 0.65 (color) 0.08 (B/W) | 1.5 (color) 0.2 (B/W) | 2 (color) 0.2 (B/W) |
| Video compression | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | H.264, Motion JPEG |
| Max video resolution (pixels) | 640 x 480 | 640 x 480 | 640 x 480 | 1280 x 1024 | 640 x 480 | 1600x900 1600x1200 | HDTV 1080i 1920x1080 HDTV 720p, 1280x720 |
| Frames per second | 30 (640x480) | 30 (640x480) | 30 (640x480) | 12 (1280x1024) 30 (800x600) | 45 (640x480) 60 (480x360) | 12 (1600x900) 9 (1600x1200) | 30 (all resolutions) |
| Audio support | | Two-way, Full Duplex | Two-way, Full Duplex | Two-way, Full Duplex | | Two-way, Half Duplex | Two-way, built-in mic, Half Duplex |
| Alarm in-/outputs | 1/1 | 1/1 | 1/1 | 1/1 | 2/1 | 2/1 | 2 configurable inputs/outputs |
| Intelligent video | Motion detection | Motion detection Audio detection | Motion detection Audio detection | Motion detection Audio detection | Motion detection Active tampering alarm | Motion detection Audio detection Active tampering alarm | Motion detection Audio detection Tampering alarm Gatekeeper |
| Security | Multi-level passwords IP filtering | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X |
| Network | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS |
| Power over Ethernet (IEEE 802.3af) | Class 2 | Class 2 | Class 2 | Class 2 | Class 2 | Class 2 | Class 3 |
| Serial connectors | | | | | RS-232, RS-485 | RS-232, RS-485 | RS-422, RS-485 |
| Outdoor use | Outdoor use requires weather-proof housing | Outdoor use requires weather-proof housing | Outdoor use requires weather-proof housing | Outdoor use requires weather-proof housing | Outdoor use requires weather-proof housing | Outdoor use requires weather-proof housing | Outdoor use requires weather-proof housing |
| Other | Changeable lens | Changeable lens | Wireless 802.11g/b, changeable lens | Changeable lens | Changeable lens | Changeable lens | SD/SDHC memory card slot and analog video out |
| Axis part # | 0198-004 | 0223-004 | 0270-004 | 0269-004 | 0221-004 | 0247-004 | 0304-001 |
| MSRP (USD) | \$599 | \$649 | \$699 | \$749 | \$999 | \$1249 | \$1499 |

1) Camera can be used with C/CS lens 2) Instant one-click pan/tilt/zoom with no moving parts 3) Requires the AXIS 213 Connection Module Axis part #22581, \$99. 4) AXIS 207W only 5) AXIS 210A only


Axis pan/tilt/zoom network cameras

| | Indoor | Indoor | Indoor / Outdoor | Indoor / Outdoor | Indoor / Outdoor | Indoor / Outdoor | Indoor / Outdoor | Indoor / Outdoor | Indoor / Outdoor |
|---|---|---|---|---|---|---|---|---|---|
| | AXIS 212 PTZ² | AXIS 212 PTZ-V² | AXIS 213 PTZ¹ | AXIS 214 PTZ¹ | AXIS 215 PTZ¹ | AXIS 215 PTZ-E | AXIS 231D+¹ | AXIS 232D+¹ | AXIS 233D |
| |  |  |  |  |  |  |  |  |  |
| | 1/2" progressive scan CMOS 3 megapixel | 1/2" progressive scan CMOS 3 megapixel | 1/4" CCD | 1/4" ExView HAD CCD | 1/4" CCD | 1/4" CCD | 1/4" ExView HAD CCD | 1/4" ExView HAD CCD | 1/4" ExView progressive scan HAD CCD |
| Lens | 2.7 mm/F1.8 fixed iris 3x instant zoom | 2.7 mm/F1.8 fixed iris 3x instant zoom | 3.5 - 91 mm auto iris and auto focus 26x optical zoom 12x digital zoom | 4.1 - 73.8 mm auto iris and auto focus 18x optical zoom 12x digital zoom | 3.8 - 46 mm auto iris and auto focus 12x optical zoom 4x digital zoom | 3.8 - 46 mm auto iris and auto focus 12x optical zoom 4x digital zoom | 4.1 - 73.8 mm auto iris and auto focus 18x optical zoom 12x digital zoom | 4.1 - 73.8 mm auto iris and auto focus 18x optical zoom 12x digital zoom | 3.4 - 119 mm auto iris and auto focus 35x optical zoom 12x digital zoom |
| Day and night | | | Configurable Built-in IR lamp | Automatic | Automatic | Automatic | | Automatic | Automatic |
| Min illumination/light sensitivity (lux) | 10 lux wide mode 20 lux tele mode | 10 lux wide mode 20 lux tele mode | 1 (color) 0.1 (B/W) | 0.3 (color) 0.005 (B/W) | 1 (color) 0.3 (B/W) | 1 (color) 0.3 (B/W) | 0.3 (color) | 0.3 (color) 0.005 (B/W) | 0.5 (color) 0.008 (B/W) |
| Video compression | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG |
| Max video resolution (pixels) | 640 x 480 | 640 x 480 | 4CIF: 704x480 | 4CIF: 704x480 | 4CIF: 704x480 | 4CIF: 704x480 | 4CIF: 704x480 | 4CIF: 704x480 | 4CIF: 704x480 |
| Frames per second | 17 (640 x 480) in overview 30 (640 x 480) at max zoom | 17 (640 x 480) in overview 30 (640 x 480) at max zoom | 30 (4CIF) | 30 (4CIF) | 30 (4CIF) | 30 (4CIF) | 30 (4CIF) | 30 (4CIF) | 30 (4CIF) |
| Pan/Tilt/Zoom | 20 presets 140° pan, 105° tilt Guard tour | 20 presets 140° pan, 105° tilt Guard tour | 20 presets 340° pan, 100° tilt | 20 presets 340° pan, 120° tilt | 20 presets 360° pan via auto-flip 180° tilt | 20 presets 360° pan via auto-flip 180° tilt | 50 presets 360° endless pan, 90° tilt, Guard tour | 50 presets 360° endless pan, 90° tilt, Guard tour | 100 presets 360° endless pan, 180° tilt, Guard tour |
| Audio support | Two-way, Half Duplex | Two-way, Half Duplex | Two-way with AXIS 213CM ³ | Two-way, Full Duplex | Two-way, Full Duplex | | | | Two-way, Full Duplex |
| Alarm in-/outputs | 1/1 | 1/1 | 2/3 with AXIS 213CM ³ | 1/1 | 1/1 | | 4/4 | 4/4 | 4/4 |
| Intelligent video | Motion detection Audio detection | Motion detection Audio detection | Motion detection | Motion detection Audio detection | Motion detection Audio detection | Motion detection | Motion detection | Motion detection | Motion detection Audio detection |
| Security | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering | Multi-level passwords IP filtering HTTPS encryption | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X | Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X |
| Network | IPv4/v6, QoS | IPv4/v6, QoS | IPv4 | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS |
| Power over Ethernet (IEEE 802.3af) | Class 1 | Class 1 | T8121 Midspan T8126 Splitter (12V) | T8121 Midspan T8126 Splitter (12V) | T8121 Midspan T8126 Splitter (12V) | | T8121 Midspan T8128 Splitter (24V) | T8121 Midspan T8128 Splitter (24V) | T8121 Midspan T8128 Splitter (24V) |
| Serial connectors | | | RS-232 with AXIS 213CM ³ | | | | | | |
| Outdoor use | | | Outdoor use requires weather-proof housing | Outdoor use requires weather-proof housing | Outdoor use requires weather-proof housing | Enclosure included -4 °F to 104 °F | Outdoor use requires weather-proof housing | Outdoor use requires weather-proof housing | Outdoor use requires weather-proof housing |
| Other | Continuous motion 24/7 | Continuous motion 24/7 Vandal-resistant | Built-in IR light up to 3 m, Analog video with AXIS 213CM ³ | | Auto-flip and E-flip | Auto-flip and E-flip | Continuous motion 24/7, WDR | Continuous motion 24/7, WDR | Continuous motion 24/7, E-flip, Image stabilizer, WDR, Auto-tracking |
| Axis part # | 0257-004 | 0280-004 | 0220-004 | 0246-004 | 0274-004 | 0306-001 | 0251-001 | 0253-001 | 0266-004 |
| MSRP (USD) | \$649 | \$699 | \$1499 | \$1299 | \$999 | \$1399 | \$1999 | \$1999 | \$2499 |











1) Camera can be used with C/CS lens 2) Instant one-click pan/tilt/zoom with no moving parts 3) Requires the AXIS 213 Connection Module Axis part #22581, \$99. 4) AXIS 207W only 5) AXIS 210A only

Axis network camera housings

Axis network camera housings

| Part # | Product | Compatible with: | MSRP |
|---|---|--|-------|
|  5015-101 | AXIS T92A10 Housing - Aluminum construction - Indoor/outdoor | AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 211M, AXIS 221, AXIS 223M, AXIS Q1755 | \$299 |
|  5010-001 | AXIS T95A00 Dome Housing ¹ - Aluminum construction - Indoor/outdoor | AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D | \$649 |
|  5010-611 | AXIS T95A61 Extension Bracket | Wall Bracket for AXIS T95A00 and T95A10 Dome Housing. | \$99 |
|  5010-641 | AXIS T95A64 Corner Bracket | Requires AXIS T95A61 Wall Bracket. | \$89 |
|  5010-671 | AXIS T95A67 Pole Bracket | Requires AXIS T95A61 Wall Bracket. | \$129 |
|  5010-101 | AXIS T95A10 Dome Housing ² - Aluminum construction - Indoor/outdoor | AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D | \$599 |
|  24886 | AXIS Indoor Fixed Wall Housing ³ | AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 221, AXIS 223M | \$299 |
|  24887 | AXIS Indoor Fixed Corner Housing ³ | | \$299 |
|  24888 | AXIS Indoor Fixed Ceiling Housing ³ | | \$199 |
|  21899 | AXIS Indoor Fixed Housing - Aluminum construction - Indoor | AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 221, AXIS 223M | \$149 |
|  22870 | AXIS Indoor Fixed Camera Dome - Steel construction - Indoor | AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 221, AXIS 223M | \$199 |
|  21898 | AXIS Indoor Recessed Enclosure - Steel construction - Indoor | AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+,AXIS 232D+, AXIS 233D | \$199 |
|  26549 | AXIS 206/207 Ceiling-Mount Housing - Steel construction - Indoor | AXIS 206, AXIS 207 (not wireless) | \$149 |
|  26550 | AXIS 206/207 Vandal-Resistant Housing - Aluminum construction - Indoor | AXIS 206, AXIS 207 (not wireless) | \$199 |
|  24889 | AXIS Outdoor Fixed Housing - Aluminum construction - Outdoor | AXIS 211, AXIS 211A, AXIS 221, AXIS 223M | \$299 |
|  29892 | AXIS Fixed Wireless Housing - Aluminum construction - Outdoor | AXIS 211W | \$499 |
|  25735 | AXIS Pendant Dome Indoor - Plastic construction - Indoor | AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+,AXIS 232D+, AXIS 233D | \$299 |
|  25733 | AXIS Pendant Dome Outdoor - Plastic construction - Indoor/outdoor | AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D | \$599 |
|  25734 | AXIS Pendant Vandal Dome - Aluminum construction - Indoor/outdoor | AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+ | \$849 |
|  25736 | Gooseneck Wall Mount | Gooseneck wall mount for the AXIS Pendant Dome | \$99 |
|  25738 | Parapet Mount | Parapet mount for the AXIS Pendant Dome | \$399 |
|  22059 | Corner Mount Adapter | Corner mount adaptor for the AXIS Pendant Indoor, Outdoor, and Vandal Dome Housings | \$89 |
|  21896 | Pole Mount Adapter | Pole mount adaptor for the AXIS Pendant Indoor, Outdoor, and Vandal Dome Housings. | \$59 |
|  26349 | Ceiling Mount 12" Extension | Secures AXIS Pendant Dome housings to hard ceilings | \$149 |
|  26350 | Ceiling Mount 24" Extension | Secures AXIS Pendant Dome housings to hard ceilings | \$169 |
| 5502-001 | AXIS 225FD Pendant Kit | Connects AXIS 225FD to 25736 and 25738 | \$69 |




Axis video encoders

| | 1-channel video encoders | | | | | | 4- and 6-channel video encoders | | | |
|--|--|--|---|--|--|--|--|---|--|---|
| | AXIS 241S  | AXIS M7001 ⁵  | AXIS 243SA  | AXIS 247S  | AXIS Q7401 ¹  | AXIS 240Q  | AXIS 241Q  | AXIS 241QA  | AXIS 243Q  | AXIS Q7406  |
| Video compression | MPEG-4, Motion JPEG | H.264, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | H.264, Motion JPEG | Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | MPEG-4, Motion JPEG | H.264, Motion JPEG |
| Max video resolution (pixels) | 4CIF: 704x480 | D1: 720x480 | 4CIF: 704x480 | 4CIF: 704x480 | D1: 720x480 | 4CIF: 704x480 | 4CIF: 704x480 | 4CIF: 704x480 | 4CIF: 704x480 | D1: 720x480 |
| Frames per second H.264 in maximum resolution | | 30 (D1) | | | 30 (D1) | | | | | 30 (D1) per channel |
| Frames per second MPEG-4 in maximum resolution | 21 (4CIF), 30 (2CIF) | | 30 (4CIF) | 27 (4CIF), 30 (VGA) | | | 21 (4CIF) using 1 channel, 20 (CIF) per channel using 4 channels | 21 (4CIF) using 1 channel, 20 (CIF) per channel using 4 channels | 30 (4CIF) per channel | |
| Frames per second Motion JPEG in maximum resolution | 30 (4CIF) | 30 (D1) | 30 (4CIF) | 30 (4CIF) | 30 (D1) | 6 (4CIF) per channel | 30 (4CIF) using 1 channel, 30 (CIF) per channel using 4 channels | 30 (4CIF) using 1 channel, 30 (CIF) per channel using 4 channels | 30 (4CIF) per channel | 30 (4CIF) per channel |
| Video source | 1 BNC composite or Y/C video input ² | 1 BNC composite input | 1 BNC composite or Y/C video input ² | 1 BNC composite input | 1 BNC composite input | 4 BNC composite inputs | 4 BNC composite inputs | 4 BNC composite inputs | 4 BNC composite inputs | 6 BNC composite inputs |
| Audio support | | | Two-way, Full Duplex | One-way | Two-way, Half Duplex | | | Two-way, Full Duplex | | |
| Alarm in-/outputs | 4/4 | | 4/4 | 1/1 | 4 configurable inputs/outputs | 4/4 | 4/4 | 4/4 | 4/4 | 2 configurable inputs/outputs per channel w/Q7900 |
| Intelligent video | Motion detection | Motion detection | Motion detection, Audio detection, Active tampering alarm | Motion detection, Audio detection | Motion detection, Audio detection, Active tampering alarm | Motion detection | Motion detection | Motion detection, Audio detection, Active tampering alarm | Motion detection, Active tampering alarm | Motion detection, Active tampering alarm |
| Pan/tilt/zoom support | ● ³ | ● ³ | ● ³ | | ● ³ | ● ³ | ● ³ | ● ³ | ● ³ | ● ³ |
| Security | Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X | Multi-level passwords, IP filtering, HTTPS encryption | Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X | Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X | Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X | Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X | Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X | Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X | Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X | Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X |
| Network | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS | IPv4/v6, QoS |
| Power over Ethernet (IEEE 802.3af) | | Class 2 | | Class 2/3 ⁴ | Class 2/3 ⁴ | | | | | |
| Serial connectors | RS-232, RS-485 | RS-422/RS-485 | RS-232, RS-485 | | RS-422/485 | RS-232, RS-485 | RS-232, RS-485 | RS-232, RS-485 | RS-485 | RS-485 |
| Standalone version | 0186-004: \$499 | 0298-001: \$299 | 0256-004: \$699 | 0272-001: \$499 | 0288-004: \$599 | 0232-004: \$499 | 0185-004: \$799 | 0230-004: \$849 | | |
| Blade version | 0210-011: \$399 | | | | | 0232-024: \$399 | 0209-011: \$699 | | 0261-001: \$999 | 0289-001: \$1499 |

1) Supports local storage with SD/SDHC card 2) Y/C video requires converter cable 3) Requires additional third-party pan/tilt/zoom device 4) Includes power output for analog camera 5) AXIS M7001 Covert Surveillance Kit also includes covert camera, at \$399 MSRP

Rack solutions

Designed for high-density installations, Axis video encoder rack solutions accommodate multiple video encoder blades in the same rack.

| | AXIS 291 1U Video Server Rack | AXIS Video Server Rack | AXIS Q7900 Rack |
|----------------------------|---|---|---|
| |  |  |  |
| Number of slots | 3 | 12 | 14 |
| Blades supported | AXIS Q7406 AXIS 240Q AXIS 241Q AXIS 241S AXIS 243Q | AXIS 240Q AXIS 241Q AXIS 241S | AXIS Q7406 AXIS 240Q AXIS 241Q AXIS 241S AXIS 243Q |
| Maximum number of channels | 18 | 48 | 84 |
| Rack size | 1U | 3U | 4U |
| Rack height | 19" | 19" | 19" |
| Built-in power supply | ● | ● | ● Redundant Power Supply |
| Network | Ethernet 10BaseT/ 100BaseTX/1000BaseT (1 Gigabit Ethernet Port) | 10BaseT/100BaseTX | Ethernet 10BaseT/ 100BaseTX/1000BaseT (4 Gigabit Ethernet Ports) |
| Axis part # | 0267-004 | 0192-004 | 0287-004 |
| MSRP | \$399 | \$1299 | \$3999 |

Accessories

AXIS 295 Video Surveillance Joystick

AXIS 295 Video Surveillance Joystick is a USB device specifically designed for responsive and accurate control of all Axis pan/tilt/zoom and dome network cameras. It features a three-axis, durable (Hall-effect) joystick and twelve programmable push-buttons. Easy to install, just connect the joystick to the USB port and control the Axis cameras.



Axis part # 0248-001

MSRP \$349

Illuminators

Illuminators for indoor/outdoor surveillance in low light or complete darkness. Use with Axis day & night cameras.



AXIS T90A11 850nm 50 Deg
AXIS T90A01 850nm 50 Deg PoE
AXIS T90A20 850nm 120-180 Deg
AXIS T90A21 850nm 50-100 Deg
AXIS T90A33 850nm 10-20 Deg
AXIS T90A40 850nm 120-180 Deg

Axis part # 5013-111
Axis part # 5013-011
Axis part # 5013-201
Axis part # 5013-211
Axis part # 5013-331
Axis part # 5013-401

MSRP \$449
MSRP \$449
MSRP \$499
MSRP \$499
MSRP \$1199
MSRP \$1699

Power-over-Ethernet Midspans and Splitters

Axis Power over Ethernet midspan and splitters offer an easy, fast and cost-effective solution for powering network video products without the need to install power outlets and electrical cabling.



High PoE midspans and splitters are available for network cameras such as PTZ and PTZ dome cameras that require higher power consumption.

Power-over-Ethernet Midspans

1-port (high PoE)
1-port
8-port
16-port

Axis part # 5014-004
Axis part # 0226-004
Axis part # 5012-004
Axis part # 5012-014

MSRP \$89
MSRP \$69
MSRP \$599
MSRP \$799

Power-over-Ethernet Active Splitters

Axis part # 5014-501 (high PoE 12V)
Axis part # 5014-511 (high PoE 24V)
Axis part # 0170-004-01¹
Axis part # 0227-001
Axis part # 5008-001 (5V)

MSRP \$89
MSRP \$89
MSRP \$89
MSRP \$89
MSRP \$89

AXIS 292 Network Video Decoder

AXIS 292 Network Video Decoder decodes digital video and audio streams into analog video signals (Axis products only).



Axis part # 0213-004

MSRP \$799

1) Not 802.3af compliant

©2009 Axis Communications AB. AXIS COMMUNICATIONS, AXIS, ETRAX, ARTPEC and VAPIX are registered trademarks or trademark applications of Axis AB in various jurisdictions. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to introduce modifications without notice.

Video management software

AXIS Camera Station

Comprehensive, easy-to-use video management software for monitoring, recording, playback and event management. Specially designed for Axis network cameras and video encoders.



10-camera base license
4-camera base license
20-camera add on license
5-camera add on license
1-camera add on license
1-year software upgrade

Axis part # 0202-004
Axis part # 0202-054
Axis part # 0202-264
Axis part # 0202-014
Axis part # 0202-034
Axis part # 0202-024

MSRP \$999
MSRP \$649
MSRP \$1979
MSRP \$499
MSRP \$99
MSRP \$149

AXIS Camera Station One


Software solution for viewing and recording live video from a single Axis network camera. Available for free download.



For more information, visit www.axis.com/products/video/software/

AXIS Camera Management

Powerful and efficient installation and management tool for Axis network video products. Available for free download.



Axis' Application Development Partners

A wide variety of software solutions for video surveillance, remote monitoring or broadcasting are available from more than 500 Axis Application Development Partners.



Distributed by: